


**SOFT CEILING LED 60X6 7540**




**SOFT CEILING LED 60X6**

painting aluminum, plastic PMMA

7540 7527

1xLED TUBE T8, max 11W, included

**SOFT CEILING LED 60X20 7526**



**SOFT CEILING LED 60X20**

painting aluminum, plastic PMMA

7538 7526

2xLED TUBE T8, max 11W, included

**SOFT WALL LED 60X6 7541**




**SOFT WALL LED 60X6**

painting aluminum, plastic PMMA

7541 7528

1xLED TUBE T8, max 11W, included

**SOFT CEILING LED 90X6 7533**



**SOFT CEILING LED 90X6**

painting aluminum, plastic PMMA

7546 7533

1xLED TUBE T8, max 16W, included

**SOFT CEILING LED 90X20 7542**




**SOFT CEILING LED 90X20**

painting aluminum, plastic PMMA

7542 7531

2xLED TUBE T8, max 16W, included

**SOFT WALL LED 90X6 7534**



**SOFT WALL LED 90X6**

painting aluminum, plastic PMMA

7548 7534

1xLED TUBE T8, max 16W, included

**SOFT CEILING LED 120X6 7536**




**SOFT CEILING LED 120X6**

painting aluminum, plastic PMMA

7536 7524

1xLED TUBE T8, max 22W, included

**SOFT CEILING LED 60X60 7530**



**SOFT CEILING LED 60X60**

painting aluminum, plastic PMMA

7544 7530

5xLED TUBE T8, max 11W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS